



CMX215

Pipe-neck condenser microphone

► Features

- Slim pipe-neck design
- Excellent sound quality & speech intelligibility
- Back electret condenser capsule
- Uni-directional (cardioid) pickup pattern
- Discreet blending in any interior or background
- Flexing gooseneck for directional placement
- Available in 45 cm and 55 cm version
- 3-pins XLR connector base

► Applications

- Conference / meeting rooms
- Presentation desks
- Houses of worship
- Auditoria
- Paging systems
- ...

The CMX215 is a pipe-neck condenser microphone fitted on a slim gooseneck with XLR base. It is particularly designed for speech reinforcement systems in a wide variation of applications, such as conference rooms, houses of worship, auditoria, ... or any other kind of speech announcement systems.

The back-electret condenser capsule with uni-directional (cardioid) characteristic reduces pickup of sound from the sides and rear, improving the speech intelligibility and eliminating unwanted noise and feedback. The high Max. input SPL guarantees a high quality sound reproduction, even when exposed to vigorous sound.

The slim pipe-neck design allows a discrete blending in any possible interior or background, while the flexing gooseneck part allows directional placement.

The microphone comes available in two versions with a length of 45 cm and 55 cm, offering a solution for any application specific placement. The shorter version is perfect for placement on tables or desks, while the longer version finds its specific application on altars, lecterns, ...

The included windscreen reduces unwanted and popping sounds.



► Specifications

SYSTEM SPECIFICATIONS	
Type	Back electret condenser
Polar pattern	Cardioid (Uni-directional)
Frequency response	50 Hz - 18 kHz
Sensitivity	45 dB \pm 3 dB / Pa (at 1 kHz)
Impedance	200 Ohm \pm 30 %
Max. SPL	130 dB (at 1kHz < 1%T.H.D)
Signal-to-noise ratio	75 dB
Power supply	10 - 52 V DC Phantom power
PRODUCT FEATURES	
Dimensions	CMX215/45: \varnothing 19 x 538 mm CMX215/55: \varnothing 19 x 638 mm
Weight net	CMX215/45: 71 g CMX215/55: 72 g
Colour	Black
Connection	3-pin XLR
SHIPPING & ORDERING	
Packaging	Carton box
Accessories included	Windscreen (MWS200/B)
Optional accessories	APM metal microphone base CMA350 microphone shock mount
Shipping weight & volume	CMX215/45: 151 g - 0.0011 Cbm CMX215/55: 160g - 0.0013 Cbm
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continuously improve our products.	