

## **M2DIS**

7" Touchscreen display kit for M2

## Features

- 7" LCD display
- Including resistive touch screen
- Live monitoring of M2 operations
- Full system configuration & control
- Password protection
- 800 x 480 pixels resolution
- Full colour display
- Integration in front panel of M2 Mixer



 Any application where the M2 matrix has to be controlled without the use of any external equipment.





The M2DIS is an optional display unit with touchscreen which can be installed internally in the front panel of the M2 Multi-Media Digital Audio Mixer.

This unit consists of a 7" TFT display panel with a resolution of 800 x 480 px that is fitted with a resistive touch-screen panel. It is controlled by a powerful 32 bit processor which communicates directly with the M2's DSP processor.

This unit allows the user to operate the control functions of the matrix systems without any external equipment. So it is now possible to set up zone selection or input mixing without any external devices. This can be useful when the system is installed in a technical room where no external control devices are within reach.

It features full configuration functions using the on-screen keyboard, allowing settings and configurations as volume control, mixing, voice file configurations, timed events, wall panel configurations, ... and many more can be done.

## **▶** Specifications

•	
PRODUCT FEATURES	
Display type	TFT-LCD
Display size	7" (178 mm)
Configuration	WVGA (16:9 diagonal)
Resolution	800 x 480 px
Colour depth	262.144 colors
Viewing angle	140°
Touchsreen type	Resistive
Processor type	32-bit
Mounting	Assembly in M2 front panel

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products